Datasheet

liniLED[®]

liniLED[®] Line Profile 20 mm

Create beautiful light lines in walls and/or ceilings with the liniLED[®] Line Profiles 20 mm. Depending on the desired effect, you can choose between diffuse or clear acrylic. Related accessories are the end caps and mountingclips.

The Line Profiles are available in white in standard lengths of 1, 2 and 3 metres. Other anodised colours on request.

For the latest version of this datasheet, visit our website: www.liniLED.com.



General Product Characteristics

Line Profile 20 mm

To be used with:

Product code	10982 (1 m), 12800 (2 m), 12801 (3 m) 12802 (4 m)
Appearance	Aluminium Profile with acrylic difuser
Size	W24 x H51 mm
Length	1000 mm, 2000 mm, 3000 mm, 4000 mm
Colour	White (RAL 9010) (other RAL colours on request)
Material	Aluminium Alloy 6060
Finish	Powder Coated
Recommended	Use the liniLED [®] U-Profile to fixate the Top LED strip (art. 11369).

Acrylic 20 mm

Product code

Size Length Max length Materials Appearance

End cap


Product code Dimensions Colour Material Finish Included

Mounting Clip


Product code Dimensions Colour Material 10959 (1 m), 12805 (2 m), 12806 (3 m) - frosted 10965 (1 m), 12810 (2 m), 12811 (3 m) - clear W20 x H6 mm 1000 mm, 2000 mm, 3000 mm 3000 mm Acrylic Diffuse (frosted) or clear

10969 W24x H51 mm White (RAL 9010) (other RAL colours on request) Aluminium Aluminium Alloy 6060 Powder Coated Screws

10977 Ø 14 mm White Nylon









2

Datasheet



